

Vise Jaw Inserts AERFCM3661

Keep Aeroquip fittings looking good even after assembly. Magnetic backed, aluminum inserts may be quickly set up and will firmly hold the hex of the fitting during assembly, without marring the finish. A horizontal pocket the entire length of the inserts holds braided hose in place, making straight cuts fast and simple.



Aluminum Dust Plugs and Caps

Keeps dirt and contamination out of oil, fuel and cooling systems when not in use.



Dash Size	NPT	Plug Part No.	Cap Part No.	No. Per Pkg.
-04	7/16"-20	AERFBM3655	AERFBM3648	20
-06	9/16"-18	AERFBM3656	AERFBM3649	20
-08	3/4"-16	AERFBM3657	AERFBM3650	20
-10	7/8"-14	AERFBM3658	AERFBM3651	12
-12	1-1/16"-12	AERFBM3659	AERFBM3652	10
-16	1-5/16"-12	AERFBM3660	AERFBM3653	10

Hose Assembly Lube AERFBM3553

A specially compounded lubricant for use in hose assembly work. Suitable for hand or machine assembly. One pint container.



ALINABAL®

Rod Ends

The Pro-Line combines high performance with economy. Includes low carbon, hardened and plated ball for corrosion resistance and a carbon fiber race that is integrally molded around the ball. Maintenance-free, Pro-Line rod ends are ideal for suspension and other components. Other Alinabal rod end series are available on a special order basis.



Part No.	Bore x Thread Size
ALIPRO-10M-G	5/8" X 5/8" RH Steel
ALIPRO-10/8M-G	1/2" X 5/8" RH Steel
ALIPRO-12M-G	3/4" X 3/4" RH Steel
ALIPRO-10ML-G	5/8" X 5/8" LH Steel
ALIPRO-10/8ML-G	1/2" X 5/8" LH Steel
ALIPRO-12ML-G	3/4" X 3/4" LH Steel
ALIALPRO-8M-G	1/2" X 1/2" RH Aluminum
ALIALPRO-8ML-G	1/2" X 1/2" LH Aluminum
ALIALPRO-10M-G	5/8" X 5/8" RH Aluminum
ALIALPRO-10ML-G	5/8" X 5/8" LH Aluminum
ALIALPRO-10/8ML-G	1/2" X 5/8" LH Aluminum
ALIALPRO-10/8M-G	1/2" X 5/8" RH Aluminum
ALIALPRO-12M-G	3/4" X 3/4" RH Aluminum
ALIALPRO-12ML-G	3/4" X 3/4" LH Aluminum
ALIALPRO-12/10M-G	5/8" X 3/4" RH Aluminum
ALIALPRO-12/10ML-G	5/8" X 3/4" LH Aluminum



ALINABAL®

Aluminum Rod Ends

Forged aluminum rod ends are ideal for the weight conscious racer. They are 41% lighter and 18% stronger than steel and include 52100 Steel hard chrome plated balls and Teflon fabric liners. Especially for race car use.



Part No.	Bore x Thread Size
ALU3A0808	1/2" x 1/2"-20 RH
ALU3A0808L	1/2" x 1/2"-20 LH
ALU3A0810	1/2" x 5/8"-18 RH
ALU3A0810L	1/2" x 5/8"-18 LH
ALU3A1010	5/8" x 5/8"-18 RH
ALU3A1010L	5/8" x 5/8"-18 LH
ALU3A1212	3/4" x 3/4"-16 RH
ALU3A1212L	3/4" x 3/4"-16 LH
ALU3A1212X	3/4" Oversize For Steering Shaft Tubing

Replacement Aluminum Crushwashers

For use with banjo fittings and carburetor adapters. Five per package.

Part No.	Dash Size	Part No.	Dash Size
AERFCM3642	-3	AERFCM3515	-8
AERFCM3513	-4	AERFCM3516	-10
AERFCM3514	-6	AERFCM3517	-12



O-Rings

Nitrile* Part No.	EPR** Part No.	Dash Size	"A"	"B"
AERFCM3472	-	-3	.301"	.064"
AERFCM3473	AERFCM3463	-4	.351"	.072"
AERFCM3474	AERFCM3464	-6	.468"	.078"
AERFCM3475	AERFCM3465	-8	.644"	.087"
AERFCM3476	AERFCM3466	-10	.755"	.097"
AERFCM3477	AERFCM3467	-12	.924"	.116"
AERFCM3497	AERFCM3468	-16	1.171"	.116"
-	AERFCM3469	-20	1.475"	.118"

*Nitrile O-rings are for use with gasoline (ten per package)

**EPR O-rings are for use w/nitromethane and alcohol (five per package)

Aluminum Tank Welding Bungs

Part No.	"A" Dash Size	"B" Dim.	"C" Dim.
AERFCM2403	-06	1.56"	.59"
AERFCM2404	-08	1.75"	.68"
AERFCM2405	-10	1.87"	.75"
AERFCM2406	-12	2.00"	.90"
AERFCM2407	-16	2.25"	.93"



Note: Use O-ring for sealing. Accepts male AN flare with hex or boss O-ring plug.