



### Brake Pedal CNC204SLMC

Floor mount pedal assembly consists of a sturdy lightweight cast aluminum bracket and a steel pedal. Accommodates two master cylinders with standard 2-1/4" bolt patterns and includes an adjustable balance bar for dial-in of front to rear bias. Pedal is 10-1/4" long for a 5.2:1 ratio. Master cylinders must be purchased separately.



### Clutch Pedal Assembly

Assembly includes lightweight cast aluminum floor-mount bracket, steel pedal and 3/4" bore master cylinder. Pedal is 10-1/4" long for a 5.2:1 ratio.

Part No.	Description
CNC252S	Bracket/Pedal/Cylinder Assembly
CNC250SLMC	Bracket and Pedal Only
CNC701F-3/4	3/4" Cylinder Only



### Single Cylinder and Steel Pedal Assembly CNC254S

Includes floor-mount lightweight cast aluminum bracket, steel pedal and 3/4" bore rectangular reservoir master cylinder. Accepts 3/16" brake line. Pedal is 10-1/4" long for a 5.2:1 ratio.



### Pedal Assembly

Swing mount assembly includes steel pedal, lightweight bracket and 3/4" bore master cylinder. Pedal, which is 12" long for a 6.2:1 ratio.

Part No.	Description
CNC262S	Bracket/Pedal/Cylinder Assembly.
CNC260SLMC	Pedal Only



### Clevis and Pin CNC1457B

Blue anodized replacement clevis assembly fits all CNC assemblies.



### Master Cylinders

Extremely lightweight master cylinders feature an American alloy casting by CNC, with 1/8" pipe thread and standard 2-1/4" mounting pattern. Overall height at reservoir is 3" on round and 4" on rectangular cylinders. Includes clevis and fitting.



Bore Size	Reservoir Style	Cylinder Part No.	Repair Kit No.
5/8"	Round	CNC701F-5/8	CNC903R
3/4"	Round	CNC701F-3/4	CNC907R
3/4"	Rectangular	CNC705F-3/4	CNC907S
7/8"	Rectangular	CNC705F-7/8	CNC911S
1"	Rectangular	CNC705F-1	CNC915S

### Master Cylinder Accessories

CNC1452	Reservoir Gasket For Round Cylinders	CNC1458
CNC1458	Rectangular Cover w/Twist Cap and Gasket	
CNC870-2	2 Lb. Residual Pressure Valve	
ALL50000	Straight Fitting 1/8"NPT To -3AN	
ALL50001	Straight Fitting 1/8"NPT To -4AN	
ALL50120	Straight Fitting 1/8"NPT To 3/16" Inv. Flare	
ALL50125	90° Fitting 1/8"NPT To 3/16" Inv. Flare	



### Hydraulic Clutch Kit CNC340SBU

Includes cast aluminum floor mount bracket, steel pedal, 3/4" CNC Girling master cylinder, and blue anodized pull style slave cylinder. 10-1/4" long pedal for a 5.2:1 ratio.



### Balance Bar Adjuster

Adjust the brake balance bar on dual master cylinder brake systems from the driver seat. By turning the knurled knob in 1/4 rotation "clicks" the front/rear brake pressure can be adjusted for changing track conditions.

Part No.	Description
CNC830-2	With 2' Cable
CNC830-3	With 3' Cable
CNC830-5	With 5' Cable



### Balance Bar CNC1215

Space saving design permits ideal front/rear braking ratio.

Part No.	Description
CNC1215	Balance Bar
CNC1216	Replacement Rod Ends For CNC1215



### Slave Cylinder

Universal slave cylinder eases clutch hookup. Equipped with 3/16" standard brake line fittings.

Part No.	Description
CNC300-BU	Blue Anodized - Pull Style
CNC300-RU	Red Anodized - Pull Style
CNC305-B	Blue Anodized - Push Style
CNC933	Repair Kit - Pull Style
CNC942	Repair Kit - Push Style
CNC1312	Adjusting Rod For Push-Style Cylinder



### Aluminum Gas Pedal CNC174S

Pedal has a built-in side foot rest, non-skid surface, 3 location mounting points, throttle stop and a built-in return spring. Overall height is 8-1/4".



### Throttle Cables and Accessories

Supreme cables are made for tight radius applications. Available in 3', 4', 5', 6', 7', 8', 10', or 12' lengths.

Part No.	Description
CNC820*	Supreme Throttle Cable
CNC841	Aluminum Half Clamp
CNC842	3/16" Ball Joint-Quick Release Cable End
CNC843	3/16" Rod End-Cable End
CNC845	Clevis and Pin-Cable End
CNC846	Hook Clamp-For Quick Cable Removal
CNC847	Cable Clamp and Shim



\*Specify Length